Docket No. CE11781JSW Customer No.. 24,273

## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Currently amended) A method on a wireless device for providing a <u>non-audible</u> pushto-talk indicator, comprising:

first indicating, via a <u>non-audible</u> push-to-talk indicator, that a user of the wireless device may not provide audio for transmission;

initiating, by the wireless device, a connection setup procedure with a wireless network; receiving a message from the wireless network indicating establishment of a connection; and

second indicating, via the <u>non-audible</u> push-to-talk indicator, that the user of the wireless device may provide audio for transmission.

- 2. (Original) The method of claim 1, wherein the first indicating comprises:
  indicating, via a push-to-talk backlit button, that a user of the wireless device may not provide audio for transmission.
- 3. (Original) The method of claim 1, wherein the first indicating comprises: indicating, via a push-to-talk backlit button that is lit in red color, that a user of the wireless device may not provide audio for transmission.

Jul 18 05 04:55p

Docket No. CE11781JSW Customer No., 24,273

5175433950

- 4. (Original) The method of claim 3, wherein the second indicating comprises: indicating, via a push-to-talk backlit button that is lit in green color, that a user of the wireless device may provide audio for transmission.
- 5. (Original) The method of claim 1, wherein the initiating, by the wireless device, a connection setup procedure with a wireless network includes the sub-step of sending a call request to the wireless network.
  - 6. (Original) The method of claim 1, further comprising: detecting the user pushing the push-to-talk button; and receiving audio from the user for transmission.
- 7. (Currently amended) A method on a wireless device for providing a non-audible pushto-talk indicator, comprising:

first indicating, via a non-audible push-to-talk indicator, that a user of the wireless device may [not] provide audio for transmission in the absence of an established call;

receiving a request to join a connection setup procedure with a wireless network; receiving a message from the wireless network indicating establishment of a connection; second indicating, via the non-audible push-to-talk indicator, that the user of the wireless device may not provide audio for transmission in response to receiving the message indicating establishment of the connection;

receiving audio from the wireless network originating from another user on another wireless device;

Docket No. CE11781JSW Customer No., 24,273

detecting the passage of a predefined period of time <u>commencing upon completion of</u>
receiving audio from the wireless network; and

[second] third indicating, via the <u>non-audible</u> push-to-talk indicator, that the user of the wireless device may provide audio for transmission.

8. (Currently amended) The method of claim 7, wherein the first, second, and third indicating comprises:

indicating, via a push-to-talk backlit button, [that] whether [[a]]the user of the wireless device may [not] provide audio for transmission.

9. (Currently amended) The method of claim 7, wherein the [first] second indicating comprises:

indicating, via [[a]] the push-to-talk backlit button that is lit in red color, that [[a]] the user of the wireless device may not provide audio for transmission.

10. (Currently amended) The method of claim 7, wherein the [second] third indicating comprises:

indicating, via [[a]] the push-to-talk backlit button that is lit in green color, that [[a]] the user of the wireless device may provide audio for transmission.

- 11. (Currently amended) A push-to-talk wireless device including a <u>non-audible</u> push-to-talk indicator, comprising:
  - a processor for initiating a connection setup procedure with a wireless network;

Docket No. CE11781JSW Customer No.. 24,273

a receiver for receiving a message from the wireless network indicating establishment of a connection;

a push-to-talk button for pushing when the user desires to provide audio for transmission; and

a <u>non-audible</u> push-to-talk indicator for indicating that the user of the wireless device may provide audio for transmission after the connection has been established and the message is received from the wireless network, otherwise for indicating that the user of the wireless device may not provide audio for transmission.

- 12. (Original) The push-to-talk wireless device of claim 11, further comprising: a transmitter for sending a call request to the wireless network when initiating a connection setup procedure with the wireless network.
- 13. (Original) The push-to-talk wireless device of claim 11, wherein the <u>non-audible</u> push-to-talk indicator comprises a backlit button.
- 14. (Original) The push-to-talk wireless device of claim 13, wherein the backlit button emits a red colored light when indicating that the user of the wireless device may not provide audio for transmission.
- 15. (Original) The push-to-talk wireless device of claim 14, wherein the backlit button emits a green colored light when indicating that the user of the wireless device may provide audio for transmission.

Docket No. CE11781JSW Customer No., 24,273

- 16. (Original) The push-to-talk wireless device of claim 11, further comprising: a detector for detecting the user pushing the push-to-talk button; and a microphone for receiving audio from the user for transmission.
- 17. (Currently amended) The push-to-talk wireless device of claim 11, wherein the nonaudible push-to-talk indicator comprises any one of:
  - a graphic;
  - a text message;
  - a light emitting device; and
  - a button.
- 18. (Currently amended) The push-to-talk wireless device of claim 17, wherein the nonaudible push-to-talk indicator emits a red colored light when indicating that the user of the wireless device may not provide audio for transmission.
- 19. (Currently amended) The push-to-talk wireless device of claim 18, wherein the nonaudible push-to-talk indicator emits a green colored light when indicating that the user of the wireless device may provide audio for transmission.
- (Currently amended) A computer readable medium on a wireless device including computer instructions for providing a non-audible push-to-talk indicator, the computer instructions including instructions for:

Docket No. CE11781JSW Customer No., 24,273

indicating, via a <u>non-audible</u> push-to-talk indicator, that a user of the wireless device may not provide audio for transmission;

initiating, by the wireless device, a connection setup procedure with a wireless network; receiving a message from the wireless network indicating establishment of a connection; and

indicating, via the <u>non-audible</u> push-to-talk indicator, that the user of the wireless device may provide audio for transmission.

21. (Original) The computer readable medium of claim 20, wherein the first instructions for indicating comprise instructions for:

indicating, via a push-to-talk backlit button, that a user of the wireless device may not provide audio for transmission.

22. (Original) The computer readable medium of claim 20, wherein the first instructions for indicating comprise instructions for:

indicating, via a push-to-talk backlit button that is lit in red color, that a user of the wireless device may not provide audio for transmission.

23. (Original) The computer readable medium of claim 22, wherein the second instructions for indicating comprise instructions for:

indicating, via a push-to-talk backlit button that is lit in green color, that a user of the wireless device may provide audio for transmission.